

# New sulfur adsorbents derived from layered double hydroxides

## II. DRIFTS study of COS and H<sub>2</sub>S adsorption

Todd J. Toops<sup>a,\*</sup>, Mark Crocker<sup>b</sup>

<sup>a</sup> Fuels, Engines and Emissions Research Center, Oak Ridge National Laboratory, 2360 Cherahala Boulevard, Knoxville, TN 37932-1563, United States

<sup>b</sup> Center for Applied Energy Research, University of Kentucky, 2540 Research Park Drive, Lexington, KY 40511-8479, United States

Received 22 August 2007; received in revised form 9 November 2007; accepted 15 January 2008

Available online 20 January 2008

### Abstract

H<sub>2</sub>S and COS adsorption were studied on two calcined layered double hydroxides (LDHs), Mg<sub>0.75</sub>Al<sub>0.25</sub>(OH)<sub>2</sub>(CO<sub>3</sub>)<sub>0.125</sub> and Mg<sub>0.65</sub>Al<sub>0.35</sub>(OH)<sub>2</sub>(CO<sub>3</sub>)<sub>0.175</sub>, using diffuse reflectance infrared Fourier transform spectroscopy (DRIFTS) and a chemisorption apparatus. Both demonstrated the ability to irreversibly adsorb H<sub>2</sub>S, corresponding to uptakes of 1.54 and 1.76 μmol/m<sup>2</sup>, respectively, but Mg<sub>0.75</sub>Al<sub>0.25</sub> had a significantly larger capacity for COS, 1.62 μmol/m<sup>2</sup> compared to 0.80 μmol/m<sup>2</sup> for Mg<sub>0.65</sub>Al<sub>0.35</sub>. Analysis of the DRIFT spectra suggests the adsorption of H<sub>2</sub>S proceeds via the substitution of lattice oxygen with sulfur, resulting in the formation of H<sub>2</sub>O on the surface. COS adsorption is more complicated, although it appears that a similar substitution of lattice oxygen with sulfur occurs. This results in the formation of CO<sub>2</sub> and subsequently bicarbonates and carbonates. The formation of hydrogen thiocarbonate is also involved, although this form is generally only observed in the later stages of adsorption and appears to form at the expense of bicarbonate. The Mg<sub>0.75</sub>Al<sub>0.25</sub> LDH retained its ability to adsorb COS in the presence of propene.

© 2008 Elsevier B.V. All rights reserved.

**Keywords:** DRIFTS; Adsorption; Carbonyl sulfide; Layered double hydroxide; Hydrotalcite

### 1. Introduction

Energy efficiency in transportation and power generation can help to conserve fossil fuel resources, as well as lessen the amount of CO<sub>2</sub> emitted to the atmosphere. A major barrier to the implementation of energy efficient technologies, however, is the presence of fuel-borne sulfur. Sulfur is a ubiquitous poison, which in both its oxidized and reduced forms (e.g., SO<sub>2</sub>, SO<sub>3</sub>; H<sub>2</sub>S, COS) can act as a catalyst poison due to its ability to adsorb strongly onto metal and metal oxide surfaces.

Fuel cells represent a particularly promising technology for clean and efficient power generation. In order to facilitate the use of coal-derived syngas or hydrocarbon fuels as feedstocks for fuel cells, the sulfur content of the feed must be reduced to very low levels. In the case of proton-exchange membrane (PEM) fuel cells, it is necessary to set the allowable sulfur concentration at levels as low as 10 ppb in order to maximize

system durability [1]. Typically sulfur in these feedstocks is present as H<sub>2</sub>S and to a lesser extent COS. Traces of mercaptans (RSH) can also be present. Removal of these compounds is necessitated by the poisoning effect that sulfur compounds exert on both water-gas shift catalysts (for syngas processing) and the platinum catalyst in the fuel cell electrodes.

In the case of a hydrocarbon fuel, direct removal of the sulfur compounds using a regenerable adsorbent is an attractive means of achieving the low sulfur level required. In the case of coal-derived syngas, the high initial sulfur level (typically around 1% H<sub>2</sub>S) requires a multi-step treating process, such as the use of an amine absorbent, followed by a polishing step. In principle, use of a solid adsorbent is an attractive option for this latter step. Unfortunately, commercial sulfur adsorbents are generally not able to achieve the very high removal efficiencies required at ambient temperature. For this reason new adsorbents are required, which combine high sorption capacity with an improved temperature range of operation.

Layered double hydroxides (LDHs) are lamellar mixed metal hydroxides and are readily synthesized via co-precipitation methods. The structure of these compounds consists of

\* Corresponding author. Tel.: +1 865 946 1207; fax: +1 865 946 1354.

E-mail address: [toopstj@ornl.gov](mailto:toopstj@ornl.gov) (T.J. Toops).

positively charged layers owing to the presence of two metal hydroxides in different oxidation states. The necessary charge balance is maintained by anions located in the interlayer region. In general, these compounds can be formulated as  $[M_{1-x}^{2+}M_x^{3+}(\text{OH})_2]A_{x/n}^{n-} \cdot m\text{H}_2\text{O}$ , the mineral hydrotalcite,  $[\text{Mg}_{0.75}\text{Al}_{0.25}(\text{OH})_2](\text{CO}_3)_{0.125} \cdot 0.5\text{H}_2\text{O}$ , being the most prominent member of this group [2]. Within the context of sulfur adsorption, LDHs are of interest due to their basicity and high surface area, which renders them excellent adsorbents for acidic species. Indeed there are literature reports of  $\text{CO}_2$  and  $\text{SO}_x$  adsorption by layered double hydroxides [3–9], while recent work has shown them to be active for COS adsorption at room temperature [10].

Further, synthetic studies have shown that LDHs possess great flexibility with respect to the degree in which their chemical and physical properties can be modified. This suggests that it should be possible to tune the properties of an LDH adsorbent so as to optimize its performance for the sorption of a given sulfur compound. However, to meet this goal, an understanding of the mechanism of adsorption is desirable. In this context, we have applied diffuse reflectance infrared Fourier transform spectroscopy (DRIFTS) to study COS and  $\text{H}_2\text{S}$  adsorption on calcined hydrotalcite.

## 2. Experimental

Two LDH samples were used in this work,  $\text{Mg}_{0.75}\text{Al}_{0.25}(\text{OH})_2(\text{CO}_3)_{0.125}$  and  $\text{Mg}_{0.65}\text{Al}_{0.35}(\text{OH})_2(\text{CO}_3)_{0.175}$ , which hereafter are respectively abbreviated as  $\text{Mg}_{0.75}\text{Al}_{0.25}$  and  $\text{Mg}_{0.65}\text{Al}_{0.35}$ . Samples were prepared according to the method of Reichle [11]. A solution of  $\text{Mg}(\text{NO}_3)_2 \cdot 6\text{H}_2\text{O}$  and  $\text{Al}(\text{NO}_3)_3 \cdot 9\text{H}_2\text{O}$  (0.4 mol total metals) in 210 ml deionized water was added dropwise at room temperature to 330 ml of an aqueous solution containing  $\text{Na}_2\text{CO}_3$  (30 g, 0.28 mol) and the calculated amount of NaOH required to react with the  $\text{M}^{2+}$  and  $\text{M}^{3+}$  ions. Vigorous stirring was maintained throughout the  $\sim 60$  min addition period. The resulting precipitate was left to age in the reaction mixture under gentle stirring at  $75^\circ\text{C}$  overnight and was subsequently isolated by a cycle of centrifuging/decanting/washing with deionized water until the washings attained a pH of 7. The resulting solid was dried at  $60^\circ\text{C}$  in a vacuum oven. The measured residual sodium content was in both cases  $< 500$  ppm. Powder X-ray diffractograms (not shown) confirmed that the LDH was the only crystalline phase present in each product.

The characterization of the LDH adsorption behavior and chemistry was performed using two capabilities. The first was a diffuse reflectance infrared Fourier transform spectroscopy (DRIFTS) instrument which employs a high temperature gas cell. The second was a chemisorption/physisorption gas cell which was used to measure specific surface area and quantify the LDH sulfur adsorption capacity. Each system was fully equipped for gas flow and heat treatments.

Before experimentation in either system the samples were heated to  $450^\circ\text{C}$  in  $\text{N}_2$  (99.999% pure) flowing at  $50\text{ cm}^3$  (STP) per minute (sccm). To monitor the impact of the thermal activation on the LDH,  $\text{N}_2$  physisorption measurements were performed in the adsorption cell according to the BET method.

The cell, described in full detail elsewhere [12], consists of a pyrex manifold for introducing gases, a U-shaped quartz sample cell, and a high-vacuum system that provides base pressures in the low  $10^{-7}$  Torr range when evacuating the manifold. The system was configured to allow gas flow through the sample cell using mass flow controllers. All o-rings in the Pyrex/stainless steel system were made of perfluoroelastomers. The sample cell was heated with a vertical furnace in conjunction with a PID temperature controller. Isotherm pressure readings were obtained using a pressure transducer with 0.01% full-scale accuracy. Fresh samples were pretreated overnight at  $450^\circ\text{C}$ , evacuated to the base pressure, and then cooled. Once thermal stability was achieved in the sample cell, the probe gas was introduced. The pure gas, either  $\text{H}_2\text{S}$  (99.5%) or COS (99.5%), was then allowed to equilibrate with the surface at pressures between 50 and 250 Torr. This was repeated to record several data points and a linear relationship between molar uptake and pressure was achieved. The reversible uptake was then measured by evacuating to the base pressure for 1 h and repeating the procedure.

The DRIFTS system has been fully detailed in earlier papers [12,13]. It consists of a MIDAC model M2500 FTIR spectrometer coupled to a Harrick Scientific barrel ellipsoidal mirror DRIFT accessory with an integrated stainless-steel reaction cell. This barrel-ellipse DRIFTS accessory is designed to maximize the collection of the diffusely scattered infrared beam; nearly  $360^\circ$  of the reflected beam is collected. The LDH materials were observed under carefully controlled temperature and gas-flow conditions. The system can be heated to  $525^\circ\text{C}$  and is typically operated at slightly below atmospheric pressure, ca. 500 Torr, to prevent stagnation in the cell and to maintain the seal between the removable hemispherical ZnSe dome and the cell body. Mass flow controllers establish the inlet gas concentrations. The reactant gases used in the measurements had the following concentrations and purities: 5% COS (99.5%) in Ar, 10%  $\text{H}_2\text{S}$  (99.5%) in Ar, and 20% propene (99+%) in Ar. All argon balance gases were ultra high purity (99.999%).

Before exposure to the sulfur containing gas mixtures, each sample was pretreated in the DRIFTS reactor cell by heating to  $450^\circ\text{C}$  and reacting with a 50 sccm flow of 1%  $\text{H}_2/\text{N}_2$ . The pretreatment was continued overnight to ensure complete transformation of the LDH into the mixed oxide. Following pretreatment, the  $\text{N}_2$  flow was continued while the sample was cooled to room temperature. While cooling from  $450^\circ\text{C}$  to room temperature, a DRIFT spectrum of the pretreated sample was recorded every  $50^\circ\text{C}$ . Once at room temperature, the cell was sealed under  $\text{N}_2$ , and the sulfur-containing gas mixture was routed through the bypass loop for 5 min to stabilize the gas mixture concentrations. For each flow condition, the sample was allowed to saturate in the sulfur-containing mixture, usually overnight. In some instances, the samples were heated to  $450^\circ\text{C}$  following saturation. Spectra were collected every  $50^\circ\text{C}$  and compared to the files recorded during the initial cooling period.

Each DRIFT spectrum is converted to absorbance units using a background spectrum that is acquired with a brushed

Table 1  
LDH properties

LDH	Surface area (m <sup>2</sup> /g)		H <sub>2</sub> S uptake (μmol/m <sup>2</sup> ) (wt% S)		COS uptake (μmol/m <sup>2</sup> ) (wt% S)	
	Initial	Treated	Total	Irreversible	Total	Irreversible
Mg <sub>0.75</sub> Al <sub>0.25</sub>	73.7	211	2.79 (1.89)	1.54 (1.04)	2.25 (1.52)	1.62 (1.10)
Mg <sub>0.65</sub> Al <sub>0.35</sub>	68.6	254	3.07 (2.50)	1.76 (1.43)	1.48 (1.21)	0.80 (0.65)

BET surface area measured with N<sub>2</sub>; H<sub>2</sub>S and COS capacity measured with static chemisorption.

aluminum plate. This file was used to convert the reflectance files into absorbance units using:

$$\text{Absorbance} = -\log_{10} \left[ \frac{\text{sample file}}{\text{background file}} \right] \quad (1)$$

Both sample and background files are temperature dependent, so a background file is recorded at each temperature of interest. Once reflectance spectra have been converted into absorbance units the spectra can be compared and even subtracted from each other for a given temperature.

### 3. Results

#### 3.1. LDH pretreatment

Thermal pretreatment of the LDHs results in both surface area changes and spectroscopic transformations. As shown in Table 1, upon pretreatment the measured BET surface area increases from 73.7 to 211 m<sup>2</sup>/g for Mg<sub>0.75</sub>Al<sub>0.25</sub> and from 68.6 to 254 m<sup>2</sup>/g for Mg<sub>0.65</sub>Al<sub>0.35</sub>. This increase in surface area upon LDH calcination has been attributed to the formation of micro- and mesopores due to expulsion of CO<sub>2</sub> and H<sub>2</sub>O from the LDH [14,15], although in this work we did not observe micropore formation. Fig. 1a and b shows the DRIFT spectra of Mg<sub>0.75</sub>Al<sub>0.25</sub> and Mg<sub>0.65</sub>Al<sub>0.35</sub> while heating from room temperature to 450 °C. To enable a direct comparison between the initial surface and pretreated surface, spectra were also recorded after cooling to room temperature. The spectral changes are similar for both samples, and after the pretreatment the spectra are nearly identical with peaks at 1534, 1412, and 1080 cm<sup>−1</sup> for Mg<sub>0.75</sub>Al<sub>0.25</sub> and 1533, 1418, and a broad peak covering 1080–1020 cm<sup>−1</sup> for Mg<sub>0.65</sub>Al<sub>0.35</sub>. These features are indicative of the presence of monodentate carbonate, the specific vibrations being listed in Table 2 for Mg<sub>0.75</sub>Al<sub>0.25</sub>.

#### 3.2. COS and H<sub>2</sub>S chemisorption

For the purposes of the DRIFTS measurements, it was decided to choose the sample with the best sulfur adsorption capacity. This was determined with static chemisorption measurements using pure H<sub>2</sub>S and COS. The isotherms for both samples are displayed in Fig. 2a for H<sub>2</sub>S and Fig. 2b for COS. The total uptake was measured for each gas, followed by evacuation for 1 h, and then the reversible uptake was measured. To determine the total and reversible uptakes, the linear isotherms are extrapolated to 225 ppm, i.e. 0.17 Torr, and









Fig. 1. Effect of thermal pretreatment on (a) Mg<sub>0.75</sub>Al<sub>0.25</sub> and (b) Mg<sub>0.65</sub>Al<sub>0.35</sub>, while heating in N<sub>2</sub> from room temperature to 450 °C and then back to room temperature. The background spectrum was a blank brushed aluminum plate recorded at each temperature.

Table 2  
DRIFTS peak assignments based on this study for adsorbates on  $\text{Mg}_{0.75}\text{Al}_{0.25}$

Hydrogen thiocarbonate	Dithiocarbonate	Bicarbonate	Monodentate carbonate	Bidentate carbonate					
									
Wavenumber (cm <sup>-1</sup> ) Bond	Wavenumber (cm <sup>-1</sup> ) Bond	Wavenumber (cm <sup>-1</sup> ) Bond	Wavenumber (cm <sup>-1</sup> ) Bond	Wavenumber (cm <sup>-1</sup> ) Bond					
Mg <sub>0.75</sub> Al <sub>0.25</sub>									
1602–11	–	1154–75	ν C–O	1645–86	ν C=O	1505–30	ν <sub>as</sub> COO <sup>–</sup>	1600–11	ν C=O
1370–90	–	1080–90	ν C–S	1405–14	ν <sub>as</sub> COO <sup>–</sup>	1408–14	ν <sub>s</sub> COO <sup>–</sup>	1260–65	ν <sub>as</sub> COO <sup>–</sup>
		1005–35	ν C–S <sub>surface</sub>	1222–25	β OH	1080–90	ν C–O	1000–35	ν <sub>s</sub> COO <sup>–</sup>
				1080–90	ν <sub>s</sub> COO <sup>–</sup>				




Fig. 2. Isotherms for (a)  $\text{H}_2\text{S}$  and (b)  $\text{COS}$  adsorption on  $\text{Mg}_{0.75}\text{Al}_{0.25}$  and  $\text{Mg}_{0.65}\text{Al}_{0.35}$ . Static chemisorption measurements recorded at  $22^\circ\text{C}$  using pure gases.

the difference in the two isotherms is taken to be the irreversible uptake. From Fig. 2, it follows that the total  $\text{H}_2\text{S}$  uptake was 2.79 and  $3.07 \mu\text{mol/m}^2$  for  $\text{Mg}_{0.75}\text{Al}_{0.25}$  and  $\text{Mg}_{0.65}\text{Al}_{0.35}$ , respectively, and after accounting for the reversible uptake, the irreversible uptake was determined to be 1.54 and  $1.76 \mu\text{mol/m}^2$ . Similarly for  $\text{COS}$ , the total uptake was 2.25 and  $1.48 \mu\text{mol/m}^2$  for  $\text{Mg}_{0.75}\text{Al}_{0.25}$  and  $\text{Mg}_{0.65}\text{Al}_{0.35}$ , respectively, and the irreversible uptake was 1.62 and  $0.80 \mu\text{mol/m}^2$ . These results are summarized in Table 1. While  $\text{Mg}_{0.65}\text{Al}_{0.35}$  demonstrated 14% more  $\text{H}_2\text{S}$  capacity, it only had half of the  $\text{COS}$  capacity of  $\text{Mg}_{0.75}\text{Al}_{0.25}$ . Due to this significant difference in performance,  $\text{Mg}_{0.75}\text{Al}_{0.25}$  was the focus of the DRIFTS study.

### 3.3. DRIFTS analysis of $\text{COS}$ and $\text{H}_2\text{S}$ adsorption

As indicated above, each sample was pretreated at  $450^\circ\text{C}$  overnight and then cooled to room temperature. A background spectrum was recorded immediately upon the temperature reaching  $22^\circ\text{C}$ , which was used as the baseline condition for the sulfur adsorption studies. At this point, the LDH was active for adsorption, and a reproducible surface had been achieved. Following adsorption the cell was purged in  $\text{N}_2$  to remove any weakly adsorbed species and to simplify the spectra from gas-phase contributions. Fig. 3a shows the spectra obtained after adsorption of 1%  $\text{H}_2\text{S}$  flowing in 50 sccm of  $\text{N}_2$  and is referenced to the initial condition such that all features shown in the figure are due to the interaction of  $\text{Mg}_{0.75}\text{Al}_{0.25}$  with the gas phase. There are significant spectral changes in the first 10 min, as the hydroxyl region ( $3000\text{--}4000 \text{ cm}^{-1}$ ) undergoes significant growth and several features arise between 1000 and  $2000 \text{ cm}^{-1}$ . Within the first 10 min there is a large peak apparent at  $1633 \text{ cm}^{-1}$ , a minor one at  $2577 \text{ cm}^{-1}$ , and a negative peak at  $3724 \text{ cm}^{-1}$ ; each of these increases modestly over the next 16 h if at all. The peak at  $2577 \text{ cm}^{-1}$  can be attributed to the H–S vibration, and since a doublet is not apparent it most likely indicates  $\text{H}_2\text{S}$  dissociative adsorption to form an M–SH species and a hydroxyl group [16,17].

As discussed in Section 4 below, among several possible routes for  $\text{H}_2\text{S}$  adsorption, reaction with surface hydroxyl groups can lead to the generation of molecularly adsorbed  $\text{H}_2\text{O}$  ( $1633 \text{ cm}^{-1}$ ). Molecularly adsorbed  $\text{H}_2\text{O}$  would contribute to






Fig. 3. Background-subtracted DRIFT spectra recorded at 22 °C of (a) 1%  $\text{H}_2\text{S}$ , (b) 225 ppm COS, and (c) 1% COS adsorption on  $\text{Mg}_{0.75}\text{Al}_{0.25}$  at various times. The background spectrum was pretreated  $\text{Mg}_{0.75}\text{Al}_{0.25}$  recorded just prior to introduction of the sulfur-containing stream.

the large hydroxyl features, and the negative peak at  $3724\text{ cm}^{-1}$  can be attributed to the initial hydroxyl group that initiated the reaction. This results in the formation of  $\text{S}^{2-}$  groups on the oxide surface, which do not have a characteristic IR absorption

frequency. Due to the relative stability of these peaks, this appears to be a kinetically fast step that is only limited by the availability of adsorption sites.

The peaks that have the most significant growth throughout the adsorption experiments are located at 1505, 1413, and  $1320\text{ cm}^{-1}$ . The feature at  $1320\text{ cm}^{-1}$  coincides with physisorbed  $\text{SO}_2$ , which could arise from the interaction of  $\text{S}^{2-}$  with trace levels of  $\text{O}_2$  in the feed or perhaps even lattice oxygen. Based on the assignments given earlier it follows that the bands at 1505 and  $1413\text{ cm}^{-1}$  correspond to monodentate carbonate, especially since there also appears to be a small amount of concurrent growth at  $1087\text{ cm}^{-1}$ . Due to the length of this experiment this adsorption is most likely due to trace amounts of  $\text{CO}_2$  in the feed. The IR bands reported in the literature for these various functional groups, as well as several other pertinent adsorbates, are listed in Table 3 for similar sulfur adsorbent materials [16,18–33].

Fig. 3b depicts the adsorption of 225 ppm COS on  $\text{Mg}_{0.75}\text{Al}_{0.25}$  at 22 °C. The spectral features that are apparent within the first 10 min occur at 1660, 1526 and  $1410\text{ cm}^{-1}$ , along with a sharp, albeit small, peak at  $1222\text{ cm}^{-1}$ . The presence of these peaks suggests the simultaneous formation of bicarbonate ( $1660$ ,  $1410$ ,  $1222$ , and  $1085\text{ cm}^{-1}$ ) and monodentate carbonate ( $1526$ ,  $1410$ , and  $1085\text{ cm}^{-1}$ ). The lack of immediately identifiable sulfur species suggests that, similar to  $\text{H}_2\text{S}$  formation, COS is reacting with the surface to form  $\text{S}^{2-}$ . After flowing the sulfur stream for 65 h there are small but significant changes in the spectra. The peak at  $1660\text{ cm}^{-1}$  is no longer significant, but instead there is a band at  $1602\text{ cm}^{-1}$  and there is some evidence of a shoulder near  $1370\text{ cm}^{-1}$ . These two peaks are proposed to correspond to hydrogen-thiocarbonate (HTC), and the spectra suggest that the bicarbonate is being converted to the sulfur containing HTC after several hours on stream. There is also substantial growth in the peaks near  $1000\text{ cm}^{-1}$ . There are many contributions at the lower wavenumbers, with one possibility being the formation of dithiocarbonate, DTC ( $1166$ ,  $1085$ , and  $1002\text{ cm}^{-1}$ );  $\text{SO}_3^{2-}$  and  $\text{HSO}_3^-$  formation are also possibilities. Also observed at long reaction times, are peaks located just below  $3000\text{ cm}^{-1}$  which correspond to saturated alkanes. These can be attributed to the presence of trace amounts of impurities in the gas feed, probably mercaptans. The feature at  $2205\text{ cm}^{-1}$  has not been identified and is not reproducible; it appears to be an artifact.

Fig. 3c shows the adsorption of 1% COS at 22 °C. Prominent peaks at 1682, 1262, and  $1225\text{ cm}^{-1}$  and broad peaks at 1408, 1313, 1090 and  $1035\text{ cm}^{-1}$  are apparent within the first hour of adsorption. Similar to the adsorption of 225 ppm COS (Fig. 3b), these peaks suggest that bicarbonate initially forms ( $1682$ ,  $1408$ ,  $1225$ , and  $1090\text{ cm}^{-1}$ ), and the lack of identifiable sulfur species at the outset continues to suggest that COS is reacting to form  $\text{S}^{2-}$ . Unlike adsorption at the lower COS concentration, there is no evidence of monodentate carbonate formation since there are no peaks apparent between 1500 and  $1600\text{ cm}^{-1}$ ; however, the presence of peaks at 1611, 1262 and  $1035\text{ cm}^{-1}$ , which start growing in after 1 h, suggest that bidentate carbonate is forming. After 4 h of adsorption, there is evidence of HTC formation (peaks at 1611 and  $1370\text{ cm}^{-1}$ ). The IR

Table 3  
Reported IR bands for adsorbates of interest on metal oxides

Wavenumber (cm <sup>-1</sup> )	Functional group	Vibration	Reference
<b>Al<sub>2</sub>O<sub>3</sub></b>			
1313–1360, 1546–1578	H-thiocarbonate	–	[18–25,28]
1151–1183	Dithiocarbonate	$\nu$ C–O	[21]
1045–1080	Dithiocarbonate	$\nu$ C–S	[21]
1009–1032	Dithiocarbonate	$\nu$ C–S <sub>surface</sub>	[21]
1648–1659	Bicarbonate	$\nu$ C=O	[18,22]
1430–1440	Bicarbonate	$\nu_{as}$ COO <sup>-</sup>	[18,22]
1230	Bicarbonate	$\beta$ OH	[18,22]
1470–1530	Monodentate carbonate	$\nu_{as}$ COO <sup>-</sup>	[16]
1300–1370	Monodentate carbonate	$\nu_s$ COO <sup>-</sup>	[16]
1040–1080	Monodentate carbonate	$\nu$ C–O	[16]
1530–1620	Bidentate carbonate	$\nu$ C=O	[16,22–24]
1250–1270	Bidentate carbonate	$\nu_{as}$ COO <sup>-</sup>	[16,22–24]
980–1020	Bidentate carbonate	$\nu_s$ COO <sup>-</sup>	[16,22–24]
1380, 1395, 1600, 2915	HCO <sub>2</sub> <sup>-</sup>	–	[25]
2570	Chemisorbed H <sub>2</sub> S and HS <sup>-</sup>	$\nu$ S–H	[16]
1620	H <sub>2</sub> O	$\delta$ H <sub>2</sub> O	[16]
1300–1330	Physisorbed SO <sub>2</sub>	$\nu_1$	[16,26]
1135–1189	Physisorbed SO <sub>2</sub>	$\nu_3$	[16,26]
970, 1050–1065	SO <sub>3</sub> <sup>2-</sup>	–	[16,26,27]
975, 1135–1148	HSO <sub>3</sub> <sup>-</sup>	–	[16,26,27]
1040, 1350	SO <sub>4</sub> <sup>2-</sup> in Al <sub>2</sub> (SO <sub>4</sub> ) <sub>3</sub>	–	[27,28]
<b>MgO</b>			
1638–1658	Bicarbonate	$\nu$ C=O	[29–31]
1405–1480	Bicarbonate	$\nu_{as}$ COO <sup>-</sup>	[31]
1217–1220	Bicarbonate	$\beta$ OH	[29–31]
1040	Bicarbonate	$\nu_s$ COO <sup>-</sup>	[31]
1506–1560	Monodentate carbonate	$\nu_{as}$ COO <sup>-</sup>	[29–31]
1385–1421	Monodentate carbonate	$\nu_s$ COO <sup>-</sup>	[29–31]
1035–1080	Monodentate carbonate	$\nu$ C–O	[29–31]
1336	Physisorbed SO <sub>2</sub>	$\nu_1$	[32]
1149	Physisorbed SO <sub>2</sub>	$\nu_3$	[32]
956, 1040–1080	SO <sub>3</sub> <sup>2-</sup>	–	[27,32]
1300–1050, 1250, 1092	SO <sub>4</sub> <sup>2-</sup> in MgSO <sub>4</sub>	–	[32]
<b>Mg–Al hydrotalcite</b>			
1650	Bicarbonate	$\nu$ C=O	[33]
1480	Bicarbonate	$\nu_{as}$ COO <sup>-</sup>	[33]
1220	Bicarbonate	$\beta$ OH	[33]
1510–1560	Monodentate carbonate	$\nu_{as}$ COO <sup>-</sup>	[33]
1360–1400	Monodentate carbonate	$\nu_s$ COO <sup>-</sup>	[33]

absorbance at 1611 cm<sup>-1</sup> has contributions from both HTC and bidentate carbonate, which are the dominant adsorbates at the end of the experiment. The minor peak at 1167 cm<sup>-1</sup> that is evident after 20 h of adsorption may represent DTC.

### 3.4. Competitive COS adsorption with propene

To be an effective trapping agent the LDH must remain active in the presence of hydrocarbons. Propene was chosen to represent a typical alkene. Fig. 4 shows the impact of 5% propene on the adsorption of 1% COS at 22 °C. Gas-phase propene has sharp spectral features at 3100, 2960, 1660, 1420, 990, and 910 cm<sup>-1</sup> which are removed from the spectra after purging. The initial adsorption product consists primarily of bicarbonate (1645, 1408, 1225, and 1090 cm<sup>-1</sup>), which shifts to both monodentate (1530, 1408, and 1090 cm<sup>-1</sup>) and bidentate (1607, 1262, and 1011 cm<sup>-1</sup>) carbonates after approximately

4 h on stream. The sulfur-containing compounds also appear to be present as both HTC (1607 cm<sup>-1</sup> and a minor shoulder at 1390 cm<sup>-1</sup>) and DTC (1175, 1090 and 1011 cm<sup>-1</sup>). While the presence of propene does have an impact on the general shape of the spectra, the end products after 16 h of adsorption are very similar to those observed in the hydrocarbon-free COS adsorption.

### 3.5. Thermal desorption after H<sub>2</sub>S and COS adsorption

After adsorbing H<sub>2</sub>S or COS on the samples, they were heated to probe the relative strength of the adsorbate bonds and to attempt to deconvolute the cluster of peaks observed between 1000 and 2000 cm<sup>-1</sup>. The spectra recorded while cooling down to room temperature after the initial pretreatment at 450 °C were used for the background files during this secondary thermal treatment. Fig. 5a shows the surface transformation of




Fig. 4. Background-subtracted DRIFT spectra at 22 °C of  $\text{Mg}_{0.75}\text{Al}_{0.25}$  while flowing 1% COS with 5% propene added. The background spectrum was pretreated  $\text{Mg}_{0.75}\text{Al}_{0.25}$  recorded just prior to introduction of the sulfur-containing stream.




Fig. 6. Background-subtracted DRIFT spectra while heating  $\text{Mg}_{0.75}\text{Al}_{0.25}$  in  $\text{N}_2$  to 450 °C after adsorbing 1% COS with 5% propene for 16 h. The background spectrum was pretreated  $\text{Mg}_{0.75}\text{Al}_{0.25}$ , which was recorded while cooling down from 450 °C during the initial pretreatment.




Fig. 5. Background-subtracted DRIFT spectra heating  $\text{Mg}_{0.75}\text{Al}_{0.25}$  in  $\text{N}_2$  to 450 °C after adsorbing (a) 1%  $\text{H}_2\text{S}$  for 16 h, and (b) 225 ppm COS for 65 h. The background spectrum was pretreated  $\text{Mg}_{0.75}\text{Al}_{0.25}$ , which was recorded while cooling down from 450 °C during the initial pretreatment.

$\text{Mg}_{0.75}\text{Al}_{0.25}$  after adsorbing  $\text{H}_2\text{S}$  for 16 h. The adsorbed water appears to dissipate quickly above 100 °C, which further reinforces this assignment. Beginning at 100 °C, and continuing to 250 °C, peaks at 1604 and 1267  $\text{cm}^{-1}$  become more prominent while spectral features between 1100 and 100  $\text{cm}^{-1}$  become very large. These observations suggest that upon heating the monodentate carbonate that was observed at 25 °C (resulting from the presence of the  $\text{CO}_2$  impurity in the feed) is converted to bidentate carbonate (1604, 1267, 1000–35  $\text{cm}^{-1}$ ). Simultaneously,  $\text{SO}_3^{2-}$  (1050–1060 and 970  $\text{cm}^{-1}$ ),  $\text{HSO}_3^-$  (1135 and 975  $\text{cm}^{-1}$ ), and perhaps sulfates (1350 and 1040  $\text{cm}^{-1}$ ) are forming, and above 400 °C, they dominate the spectra. The oxygen required for the formation of these sulfur species presumably derives from the Mg–Al mixed oxide, although we cannot rule out the possibility that trace oxygen in the feed may have contributed to the formation of these oxidized species.

Fig. 5b shows the spectra recorded during the thermal treatment following COS adsorption. As in the  $\text{H}_2\text{S}$  case, bidentate carbonate (1602, 1275, 1000–35  $\text{cm}^{-1}$ ) forms between 25 and 250 °C, but here HTC (1602 and 1370  $\text{cm}^{-1}$ ) is also observed while heating to 250 °C. Above 300 °C,  $\text{SO}_3^{2-}$ ,  $\text{HSO}_3^-$ , and bulk sulfates dominate the spectra. The final spectrum is very similar to the  $\text{H}_2\text{S}$  case.


Fig. 6 shows the surface transformation of  $\text{Mg}_{0.75}\text{Al}_{0.25}$  after adsorbing 1% COS in the presence of 5% propene for 16 h. The observed trends are nearly identical to the propene-free case, where bidentate carbonate (1610, 1262, 1000–35  $\text{cm}^{-1}$ ) and HTC (1610 and 1389  $\text{cm}^{-1}$ ) are evident up to 250 °C and  $\text{SO}_3^{2-}$ ,  $\text{HSO}_3^-$ , and bulk sulfates dominate the spectra at higher temperatures. Again, the final spectrum in this case is very similar to both the  $\text{H}_2\text{S}$ - and COS-only experiments.

#### 4. Discussion



As shown in Fig. 3a, exposure of calcined hydrotalcite to  $\text{H}_2\text{S}$  results in the formation of a band at 2577  $\text{cm}^{-1}$  which can




be assigned to surface SH groups. Concomitantly, spectral changes in the hydroxyl region suggest both the creation of new hydroxyl groups, as well as the consumption of free hydroxyl groups, the latter evidenced by the appearance of a negative band at  $3724\text{ cm}^{-1}$ . Similar observations have been reported for  $\text{H}_2\text{S}$  adsorption on a variety of oxides [16,17], for which it was suggested that adsorption proceeds via  $\text{H}_2\text{S}$  dissociation, e.g.:




Another adsorption route that seems particularly plausible on mixed oxides is through the interaction of  $\text{H}_2\text{S}$  with a defective site, or oxygen vacancy, resulting in incorporation of  $\text{S}^{2-}$  in the lattice. As detailed by Davydov et al. for  $\text{Al}_2\text{O}_3$  [16], this involves the consumption of a hydroxyl group and the formation of molecularly adsorbed  $\text{H}_2\text{O}$  (as well as a new hydroxyl group), which fits well with the spectroscopic data:




Additionally, in the case of  $\text{MgO}$ , its high basicity makes it probable that  $\text{S}^{2-}$  can be incorporated directly into the surface [16], i.e.:



In the case of  $\text{COS}$  adsorption, the total absence of identifiable sulfur species at short reaction times suggests a similar incorporation of  $\text{S}^{2-}$ . Indeed, Haag and Miale found that the surface of  $\text{MgO}$  underwent sulfidation when exposed to  $\text{COS}$  at  $811\text{ K}$  (contact times being on the order of seconds) [34]:




A thiocarbonate intermediate was proposed for this reaction [34], although our DRIFTS data are unable to provide evidence of such an intermediate. The  $\text{CO}_2$  produced is evidently adsorbed on the surface, giving rise to the observed bicarbonate together with either monodentate and/or bidentate carbonate. At longer reaction times two types of sulfur-containing species are observable, corresponding to HTC and DTC. The fact that growth of the HTC band is simultaneous with a decrease in the intensity of the bicarbonate bands suggests that the HTC is derived from the bicarbonate. Lavalley et al. have reported that when  $\text{H}_2\text{S}$  is adsorbed on  $\text{CO}_2$ -treated  $\gamma$ -alumina, the carbonate bands are weakened and new bands appear at  $1570$  and  $1340\text{ cm}^{-1}$  which can be assigned to HTC [17]:




The origin of the required  $\text{H}_2\text{S}$  is unclear, although it may be derived from the hydrolysis of  $\text{M}-\text{SH}$  ( $\text{M} = \text{Mg}$  or  $\text{Al}$ ) or lattice

$\text{S}^{2-}$  species (i.e., the reverse of reactions (2) and (4)) by adventitious water.

At long reaction times DTC is also observed. Lavalley and co-workers [21] have established that this is formed upon adsorption of  $\text{CS}_2$  onto basic  $\text{O}^{2-}$  sites in metal oxides:



The presence of  $\text{CS}_2$  can in turn be rationalized based on the ability of  $\text{COS}$  to undergo disproportionation:



Haag and Miale [34] showed that metal oxides are able to catalyze this reaction,  $\text{MgO}$  being a particularly efficient catalyst; at  $538^\circ\text{C}$ , 90% attainment of equilibrium was observed at a contact time of  $0.2\text{ s}$ . Although the equilibrium constant for this reaction is very small at room temperature ( $2.4 \times 10^{-3}$  based on the reported value of  $\Delta G^\circ$  [34]), removal of the  $\text{CS}_2$  and  $\text{CO}_2$  products by adsorption may enable non-equilibrium surface concentrations of  $\text{CS}_2$  to accumulate.

Overall, the mechanism of  $\text{COS}$  adsorption on calcined hydrotalcite is rather different to that observed for less basic oxides (such as  $\text{Al}_2\text{O}_3$ ,  $\text{ZrO}_2$  and  $\text{TiO}_2$ ). For the latter, it is well established that  $\text{COS}$  adsorption occurs primarily via the formation of HTC species (the primary product), which can undergo hydrolysis to afford  $\text{CO}_2$  and  $\text{H}_2\text{S}$  which are in turn adsorbed [35,36]. In the case of calcined hydrotalcite, the strongly basic surface reacts with  $\text{COS}$  to generate  $\text{S}^{2-}$  species and  $\text{CO}_2$ , the latter being adsorbed mainly in the form of bicarbonate.

## 5. Conclusions

Both  $\text{Mg}_{0.65}\text{Al}_{0.35}$  and  $\text{Mg}_{0.75}\text{Al}_{0.25}$  demonstrated the ability to adsorb significant concentrations of  $\text{H}_2\text{S}$  and  $\text{COS}$  at  $25^\circ\text{C}$ . The adsorption of  $\text{H}_2\text{S}$  proceeds via the substitution of lattice oxygen with sulfur which results in the formation of  $\text{H}_2\text{O}$  on the surface of the calcined LDH.  $\text{COS}$  adsorption is more complicated, although it appears that a similar substitution of lattice oxygen with sulfur is taking place. This results in the formation of  $\text{CO}_2$  and subsequently bicarbonates and carbonates. The formation of hydrogen thiocarbonate is also involved, although this form is generally only observed in the later stages of adsorption and appears to form at the expense of bicarbonate. The  $\text{Mg}_{0.75}\text{Al}_{0.25}$  LDH retained its ability to adsorb  $\text{COS}$  in the presence of propene.

## Acknowledgements

The authors thank Dr. Louis Powell of the Oak Ridge Y-12 National Security Complex for use of the FTIR spectrometer and DRIFTS accessory. This research was sponsored by the State Partnership Program at Oak Ridge National Laboratory, which is managed by UT-Battelle, LLC, under US Department of Energy contract number DE-AC05-00OR 22725.



## References

- [1] R. Farrauto, S. Hwang, L. Shore, W. Ruettinger, J. Lampert, T. Giroux, Y. Liu, O. Ilinich, *Annu. Rev. Mater. Res.* 33 (2003) 1.
- [2] F. Cavani, F. Trifiró, A. Vaccari, *Catal. Today* 11 (1991) 173.
- [3] Z. Yong, A.E. Rodrigues, *Energy Convers. Manage.* 43 (2002) 1865.
- [4] T. Yamamoto, T. Kodama, N. Hasegawa, M. Tsuji, Y. Tamaura, *Energy Convers. Manage.* 36 (1995) 637.
- [5] M. Tsuji, G. Mao, T. Yoshida, Y. Tamaura, *J. Mater. Res.* 8 (1993) 1137.
- [6] A.E. Palomares, J.M. López-Nieto, F.J. Lázaro, A. López, A. Corma, *Appl. Catal. B* 20 (1999) 257.
- [7] A. Corma, A.E. Palomares, F. Rey, F. Márquez, *J. Catal.* 170 (1997) 140.
- [8] E.W. Albers, H.W. Burkhead Jr., US 5,928,496 (1999).
- [9] T.J. Pinnavaia, J. Amarasekera, US 5,358,701 (1994).
- [10] D.E. Sparks, T. Morgan, P.M. Patterson, S.A. Tackett, E. Morris, M. Crocker, T.J. Toops, *Appl. Catal. B* 82 (2008) 190–198.
- [11] W.T. Reichle, *J. Catal.* 94 (1985) 547.
- [12] T.J. Toops, D.B. Smith, W.P. Partridge, *Appl. Catal. B* 58 (2005) 245.
- [13] G.L. Powell, M. Milosevic, J. Lucania, N.J. Harrick, *Appl. Spectrosc.* 46 (1992) 111.
- [14] W.T. Reichle, S.Y. Kang, D.S. Everhardt, *J. Catal.* 101 (1986) 352.
- [15] F. Rey, V. Fornes, J.M. Rojo, *J. Chem. Soc., Faraday Trans.* 88 (1992) 2233.
- [16] A.A. Davydov, in: C.H. Rochester (Ed.), *Infrared Spectroscopy of Adsorbed Species on the Surface of Transition Metal Oxides*, John Wiley & Sons, Chichester, England, 1990.
- [17] J.C. Lavalley, J. Travert, T. Chevreau, J. Lamotte, O. Saur, *J. Chem. Soc., Chem. Commun.* (1979) 146.
- [18] E. Laperdrix, I. Justin, G. Costentin, O. Saur, J.C. Lavalley, A. Aboulayt, J.L. Ray, C. Nedež, *Appl. Catal. B* 17 (1998) 167.
- [19] J.C. Lavalley, *Catal. Today* 27 (1996) 377.
- [20] C. Rhodes, S.A. Riddell, J. West, B.P. Williams, G.J. Hutchings, *Catal. Today* 59 (2000) 443.
- [21] A. Sahibed-Dine, A. Aboulyat, M. Bensitel, A.B.M. Saad, M. Daturi, J.C. Lavalley, *J. Mol. Catal. A* 162 (2000) 125.
- [22] C. Morterra, C. Emanuel, G. Cerrato, G. Magnacca, *J. Chem. Soc., Faraday Trans.* 173 (1977) 1544.
- [23] M. Kantschewa, E.V. Albano, G. Ertl, H. Knözinger, *Appl. Catal.* 8 (1983) 71.
- [24] P. Chaumette, P. Courly, J. Barbier, T. Fortin, J.C. Lavalley, C. Chauvin, A. Kiennemann, H. Idriss, R.P.A. Sneed, B. Denise, in: *Proceedings of the 9th International Congress on Catalysis*, vol. 2, Chem. Inst. Can., Ottawa, 1988, p. 585.
- [25] A. Jordan, M.I. Zakiz, C. Kappenstein, *Phys. Chem. Chem. Phys.* 6 (2004) 2502.
- [26] A. Datta, R.G. Cavell, R.W. Tower, Z.M. George, *J. Phys. Chem.* 89 (1985) 443.
- [27] X. Zhang, G. Zhuang, J. Chen, Y. Wang, X. Wang, Z. An, P. Zhang, *J. Phys. Chem.* 110 (2006) 12588.
- [28] Ch. Sedlmair, K. Seshan, A. Jentys, J.A. Lercher, *Catal. Today* 75 (2002) 413.
- [29] V.A. Ivanov, A. Piéplu, J.C. Lavalley, P. Nortier, *Appl. Catal. A* 131 (1995) 323.
- [30] R. Philipp, K. Fujimoto, *J. Phys. Chem.* 96 (1992) 9035.
- [31] J.V. Stark, D.G. Park, I. Lagadic, K.J. Klabunde, *Chem. Mater.* 8 (1996) 1904.
- [32] A.J. Goodsel, M.J.D. Low, N. Takezawa, *Environ. Sci. Technol.* 6 (3) (1972) 369.
- [33] J.I. Di Cosimo, V.K. Diez, M. Xu, E. Iglesia, C.R. Apesteguia, *J. Catal.* 178 (1998) 499.
- [34] W.O. Haag, J.M. Miale, in: *Proceedings of the 6th International Congress on Catalysis*, London, Vol. 1, 1976, p. 397.
- [35] P.E. Hoggan, A. Aboulayt, A. Pieplu, P. Nortier, J.C. Lavalley, *J. Catal.* 149 (1994) 300.
- [36] J. Bachelier, A. Aboulayt, J.C. Lavalley, O. Legendre, F. Luck, *Catal. Today* 17 (1993) 55.